



engine drive **powerblast** sprayer

single **38"** diameter fan

length	21'
height	63"-70" to fan housing/adjustable
width	100" (21.5L-16.1/adjustable axle)
tire options	16.5L-16.1 rib or terra 21.5L-16.1 rib or terra 11.25-24 rib
axle options	multiposition adjustable fixed offset (specify)

John Deere <i>Powertech</i> 4.5L diesel engine 173 horsepower Tier III turbocharged	38" diameter 9 blade stainless steel axial flow fan operating @2200RPM
Electric throttle	SS304 stainless steel blower housing
Vibration dampener on flywheel minimizes drivetrain vibration	Electric fan clutch
Large surface easy clean radiator	Lower air scoops
74 gallon fuel capacity	500 gallon stainless steel tank stainless steel plumbing, lid assembly stainless steel large paddle mechanical agitation stainless steel tank rails, engine shroud
Safety shut down system Oil pressure Water temperature	2" NPT Quick-Fill fittings front & rear of tank
Control from the cab Throttle Spray manifold Dump valve Emergency Shut Down	Rears RPA centrifugal pump 80GPM/200PSI Electric pump clutch
Cab mounted instrumentation Tachometer Oil pressure Water temperature Fuel level Hour meter Air cleaner service indicator Programmable throttle settings	Electric spray controls Electric dump valve Suction and discharge line strainers are easily isolated for cleaning during operation Dual pressure strainers Oversize suction line strainer with large surface area screen element and stainless steel housing
Work Lights	Rollover nozzles with ceramic tips Diaphragm check valves on each nozzle for positive shut-off
	Adjustable swivel hitch

**For more information,
or the location of your nearest dealer,
please call 800.547.8925**

Our promotionals are printed on recycled paper.
Please keep this circle going. Recycle this sheet.



Litho USA

rears manufacturing company. eugene. oregon. 1 800 547 8925

REARS