REARS

Engine Drive Powerblast 33" single fan






Top and inset, above, 500 gallon tank with standard frame, 33" fan.


At right, 400 gallon tank with narrow frame and 38" fan/housing.



500 or 600 gallon tank with standard frame



400 gallon tank with narrow frame



unit length 19' 10" 500 gallon standard or 400 gallon narrow

engine drive **powerblast** sprayer single **33"** diameter fan

John Deere Powertech 4.5L diesel engine -115 horsepower turbocharged

Electric throttle -

Vibration dampener on flywheel minimizes drivetrain vibration

Large surface easy clean radiator -

50 gallon fuel capacity 500 & 600G units -40 gallon fuel capacity 400G Narrow



400 Narrow w/33" fan

Safety shut down system Oil pressure 80GPM/200PSI Water temperature Electric pump clutch Control from the cab -Electric spray controls Throttle Spray manifold Electric dump valve Dump valve **Emergency Shut Down** Instrumentation -Ammeter Tachometer Oil pressure Water temperature Hour meter for positive shut-off Air cleaner service indicator Adjustable swivel hitch Multiposition axles or fixed offset Work lights Tire options TERRA 13.5-16.1 14L-16.1 RIB 16.5L-16.1 RIB/TERRA please call 800.547.8925 RIB/TERRA 12.5L-16.1 11.25-24 RIB



33" diameter 9 blade stainless steel axial flow fan operating @2200RPM

SS304 stainless steel blower housing

Electric fan clutch

Lower air scoops

-Stainless steel tank: 500, 600, 400 Narrow stainless steel plumbing, lid assembly stainless steel large paddle mechanical agitation stainless steel tank rails, engine shroud

2"NPT Quick-Fill fittings front & rear of tank

Rears RPA centrifugal pump

Suction line and discharge line strainers are easily isolated for cleaning Oversize suction line strainer with large surface

area screen element and Stainless Steel housing

Rollover nozzles with ceramic tips

Diaphragm check valves on each nozzle

For more information. or the location of your nearest dealer,



500 Standard w/33" fan

rears manufacturing company. eugene. oregon. 1 800 547 8925